

SPECIFICATIONS OF COMPRESSOR

Model No: 3CB100SA0M

Output : 6 HP



Panasonic Appliances Compressor (Dalian) Co.,Ltd.

02/Sep/19




GENERAL SPECIFICATIONS

Model No:		3CB100SA0M
Application		
Evaporating Temp Range	(°C)	-25 ~ 10
Refrigerant		R404A
Compressor Cooling		Natural Cooling
Rated Performance		
Capacity	(W)	11800
Input	(W)	4,800
Current	(A)	8.4
Revolution	(min ⁻¹)	2950
Sound Level	(dB(A))	65max
Rating Conditions		
Power Source		3-PH 50Hz 380-415V
Evaporating Temp	(°C)	-6.5
Condensing Temp	(°C)	43.5
Suction Gas Temp	(°C)	18.5
Liquid Temp	(°C)	43.5
Ambient Temp	(°C)	35.0
Measuring Point of Sound Level		
Distance from the Compressor	(m)	1.0
Compressor		
Design		Hermetic Scroll
Displacement	(cm3)	100.0
Suction Line Connection	(Φ mm OD)	22.22
Discharge Line Connection	(Φ mm OD)	12.7
Oil	(ml)	1700 (FV68S)
Mass(Incl.Oil)	(kg)	38
Motor		
Type		3-PH Induction Motor(3IR)
Pole		2
Rated Power Source		3-PH 50Hz 380-415V
Voltage Range	(V)	342~456
Starting Current	(A)	-

Panasonic Appliances Compressor (Dalian) Co.,Ltd.

PERFORMANCE CURVE

Code No.	3CB100SA0M
Power Source	3-PH 50Hz 380-415V
Condensing Temp.(°C)	20、30、35、40、43.5、50、55、60
Suction Gas Temp.(°C)	18.5
Sub Cooled(K)	0
Compressor Cooling	Natural Cooling
Refrigerant	R404A



PERFORMANCE DATA

Code No.	3CB100SA0M
Power Source	3-PH 50Hz 380-415V
Condensing Temp.(°C)	20、30、35、40、43.5、50、55、60
Suction Gas Temp.(°C)	18.5
Sub Cooled(K)	0
Compressor Cooling	Natural Cooling
Refrigerant	R404A

Capacity (W)

		Evaporating Temp. (°C)							
		-25	-20	-15	-10	-6.5	0	5	10
Condensing Temp. (°C)	20.0	8,790	10,280	12,440	15,250	17,620	22,870		
	30.0	7,450	8,760	10,590	12,940	14,890	19,200	23,110	27,550
	35.0	6,840	8,070	9,750	11,900	13,670	17,560	21,080	25,050
	40.0	6,290	7,430	8,980	10,930	12,540	16,040	19,200	22,760
	43.5	5,920	7,010	8,470	10,300	11,800	15,060	17,990	21,280
	50.0		6,300	7,610	9,230	10,550	13,400	15,950	18,800
	55.0			7,020	8,500	9,700	12,270	14,570	17,130
	60.0				7,840	8,940	11,270	13,350	15,670

Input (W)

		Evaporating Temp. (°C)							
		-25	-20	-15	-10	-6.5	0	5	10
Condensing Temp. (°C)	20.0	2,670	2,750	2,830	2,900	2,960	3,070		
	30.0	3,310	3,390	3,470	3,560	3,620	3,730	3,820	3,910
	35.0	3,700	3,780	3,870	3,950	4,010	4,130	4,220	4,310
	40.0	4,140	4,230	4,310	4,400	4,460	4,580	4,670	4,760
	43.5	4,480	4,570	4,650	4,740	4,800	4,920	5,010	5,100
	50.0		5,260	5,350	5,430	5,490	5,610	5,700	5,790
	55.0			5,940	6,030	6,090	6,200	6,280	6,370
	60.0				6,670	6,720	6,830	6,910	7,000

Current (A)

		Evaporating Temp. (°C)							
		-25	-20	-15	-10	-6.5	0	5	10
Condensing Temp. (°C)	20.0	5.4	5.4	5.5	5.6	5.6	5.6		
	30.0	6.1	6.3	6.4	6.5	6.6	6.7	6.7	6.7
	35.0	6.5	6.8	7.0	7.1	7.2	7.3	7.4	7.4
	40.0	7.0	7.3	7.5	7.7	7.9	8.0	8.1	8.1
	43.5	7.3	7.7	8.0	8.2	8.4	8.5	8.6	8.6
	50.0		8.5	8.9	9.2	9.3	9.6	9.6	9.6
	55.0			9.6	10.0	10.2	10.4	10.5	10.5
	60.0				10.8	11.0	11.4	11.5	11.5

Coefficients of Polynomial Formula

	Capacity (W)	Input (W)	Current (A)
C1	3.169732E+04	2.308059E+03	4.289258E+00
C2	1.239230E+03	1.339731E+01	1.923126E-02
C3	-4.939793E+02	1.940208E+01	4.316197E-02
C4	1.718048E+01	5.997209E-02	8.855067E-04
C5	-1.957053E+01	2.318891E-01	-9.077871E-04
C6	2.565437E+00	9.330741E-01	1.242477E-03
C7	-2.012599E-03	-5.392548E-06	4.196604E-07
C8	-2.259415E-01	-9.077429E-04	-4.729153E-05
C9	8.619154E-02	-2.912073E-03	2.017987E-05
C10	-7.364922E-08	3.472528E-08	3.135631E-11

Note: The polynomial coefficients subject to change without notice.

$X = C1 + C2*(S) + C3*D + C4*(S^2) + C5*(S*D) + C6*(D^2) + C7*(S^3) + C8*(D*S^2) + C9*(S*D^2) + C10*(D^3)$

X—CAPACITY(W) OR POWER(W) OR CURRENT(A)

S—EVAPORATING TEMP, °C

D—CONDENSING TEMP, °C

Operating Envelope

Refrigerant : R404A

Suction Gas Temp:18.5℃

Sub Cooled: 0 K

