



Minimum evaporating temp. with:
 ——— 25°C Suction Gas Return
 - - - 10K Suction Superheat

Suction Superheat 10,0K

Evaporating Temperature °C

Liquid subcooling 0,0K

Cond °C	Capacity kW											
	-20	-15	-10	-5	0	5	7	10	12,5	15	20	
10	31,50	38,50	46,70	56,40	60,30	72,30						
20	27,90	34,30	41,60	50,20	54,70	65,30	70,00	77,60	84,60	92,10		
30	24,80	31,00	37,80	45,70	49,90	59,50	63,80	70,60	76,80	83,50	98,40	
40	21,10	27,40	34,20	41,60	49,90	59,50	63,80	70,60	76,80	83,50	98,40	
45		25,30	32,10	39,40	47,50	56,80	60,80	67,40	73,30	79,60	93,70	
50			29,60	36,90	45,00	53,90	57,80	64,10	69,70	75,80	89,20	
55				34,10	42,00	50,80	54,60	60,70	66,10	71,90	84,70	
60					38,70	47,30	51,10	57,00	62,20	67,80	80,10	
65					34,70	43,40	47,00	52,80	57,90	63,30		
	Power Input kW											
	-20	-15	-10	-5	0	5	7	10	12,5	15	20	
10	5,79	5,94	6,14	6,37	8,75	9,02						
20	8,00	8,14	8,31	8,51	10,80	11,00	11,10	11,25	11,40	11,55		
30	10,15	10,25	10,40	10,60	13,10	13,25	13,35	13,45	13,55	13,65	13,90	
40	12,55	12,65	12,80	12,95	14,45	14,60	14,65	14,75	14,85	14,95	15,15	
45		14,05	14,20	14,30	16,00	16,15	16,20	16,25	16,35	16,40	16,60	
50			15,75	15,90	17,80	17,90	17,95	18,00	18,05	18,15	18,25	
55				17,70	19,85	19,95	20,00	20,00	20,10	20,10	20,20	
60					22,20	22,30	22,30	22,40	22,40	22,40		
65												
	Current 400V, A											
	-20	-15	-10	-5	0	5	7	10	12,5	15	20	
10	14,88	15,03	15,22	15,45	18,18	18,46						
20	17,39	17,55	17,73	17,94	20,59	20,82	20,93	21,08	21,22	21,36		
30	19,83	19,99	20,17	20,37	23,43	23,64	23,72	23,85	23,96	24,07	24,31	
40	22,71	22,88	23,06	23,24	25,19	25,37	25,44	25,56	25,66	25,76	25,96	
45		24,66	24,83	25,01	27,24	27,41	27,47	27,57	27,66	27,74	27,91	
50			26,91	27,07	29,66	29,81	29,87	29,96	30,03	30,10	30,23	
55				29,51	32,52	32,65	32,70	32,77	32,83	32,88	32,99	
60					35,87	35,98	36,02	36,08	36,12	36,16		
65												
	Mass Flow g/s											
	-20	-15	-10	-5	0	5	7	10	12,5	15	20	
10	164,00	198,00	237,00	284,00	320,00	379,00						
20	155,00	188,00	226,00	269,00	310,00	366,00	391,00	431,00	467,00	506,00		
30	148,00	182,00	220,00	262,00	306,00	360,00	384,00	423,00	457,00	494,00	576,00	
40	136,50	175,00	215,00	258,00	300,00	355,00	379,00	417,00	451,00	487,00	567,00	
45		168,00	210,00	255,00	304,00	358,00	382,00	420,00	454,00	490,00	571,00	
50			203,00	250,00	295,00	351,00	376,00	414,00	448,00	484,00	564,00	
55				242,00	285,00	345,00	369,00	409,00	443,00	480,00	560,00	
60					271,00	334,00	360,00	401,00	436,00	474,00		
65												

Copeland Scroll - Compressor - Air Conditioning - Standard
COMPRESSOR MECHANICAL AND PHYSICAL DATA

Displacement @ 50 Hz, cu.m/h	56.6
Length/Width, mm	432/376
Height, mm	717
Net Weight, kg	140
Gross Weight, kg	168
Rotalock Suction, inch	2 1/4 x 12 UN
Rotalock Discharge, inch	1 3/4 x 12 UN
Stub Suction, inch	1 5/8 ID
Stub Discharge, inch	1 3/8 ID
Oil Quantity, l	4.7
Base mounting (hole dia), mm	266.7 x 266.7 (22.6)
Sound Pressure @ 1m (HT), dBA	72
Sound Power (HT), dBA	83
PED Category	2
Internal Free Volume, l	26.9
High Side PS, bar(g)	32
Low Side PS, bar(g)	20
Low Side TS Max., °C	52
Low Side TS Min., °C	-35

COMPRESSOR ELECTRICAL DATA (380/420V - 3~ - 50Hz)

Maximum Operating Current, A	41
Locked Rotor Current, A	225
Winding Resistance, ohm	0.63
Default Enclosure Class	IP 54 (IEC 34)

ACCESSORIES INCLUDED

Discharge Temperature Protection	Internal Thermistor
Discharge Temperature Protection	PTC in Scroll Discharge Port
Enclosure Class	IP 54
Motor Protection Device	INT69SC2
Mounting Grommets	Standard
Oil Service Valve	Schraeder Valve
Check Valve (NRV)	Discharge Low Leak Check Valve

ACCESSORIES OPTIONAL

Crankcase Heater	120 W External
Mounting Grommets	Rubber Grommet For Single
Mounting Grommets	Rubber Grommet For Parallel Operation
Adapter Kit	R1"3/4 - B1"3/8 For TPTL for Parallel Operation
Oil Control System	ALCO Trax-Oil OM3

MOTOR OPTIONS

Power Supply	Nominal Voltage	Motor Code	Start Connection	DOL Connection	Amps Factor
380-420 V/3~/50H	400	TWD		Y	1,00
200 V/3~/50Hz	200	TWC		Y	2,09
208-230 V/3~/60H	230	TWC		Y	2,09
575 V/3~/60Hz	575	TWE		Y	0,80
380 V/3~/60Hz	380	TW7		Y	1,26
460 V/3~/60Hz	460	TWD		Y	1,00