

ENGINEERING  
TOMORROW

*Danfoss*

Data sheet

# Micro Plate Heat Exchanger

## Save you time and money


D62

**24/7**

ordering from stock  
quick and easy  
deliveries from stock.

# D62 - increased flexibility and savings

## Micro Plate Heat Exchanger



Flow design in MPHE



Flexible two-in-one connection



Innovative micro plate design



Scan QR code for more technical information and code numbers

### Introduction

The new Danfoss D62 is an excellent route to increased savings. With a robust and resource-efficient design, the D62 is designed to operate efficiently year after year in a whole range of applications. The innovative D62 channel plate pattern makes it the best heat exchanger on the market, significantly reducing energy consumption and lowering CO<sub>2</sub> emissions. The D62 has a capacity of 20-90 kW and is suitable for evaporators, condensers and one-phase applications. Thanks to the two-in-one connection it is always easier to install. The D62 is the natural choice for any application.

### Key features

- Standard- and high-pressure designs make it the ideal solution for any application or refrigerant
- Two-in-one connection for easy installation
- With innovative micro plate channel plate pattern for higher heat transfer to minimize weight and refrigerant charge

### Easy installation

A D62 heat exchanger is always easier to use. Every product is delivered with Danfoss two-in-one connections, which allow both threading and soldering. The universal soldering connections are suitable for both customary/imperial and metric piping.

### Technical data

n = number of plates

The D62 product is available in different configurations:

D62: approved to 30 bar

D62-H: Special (high-theta) pattern for high heat transfer

D62L-E: High-pressure Evaporator, approved to 45 bar

D62-E: Evaporator with refrigerant distributor

D62L: High-pressure, approved to 45 bar

D62L-H: High-pressure, high-theta, approved to 45 bar

Model	A (mm/inch)	Min/Max. working temperature	Max. working pressure	Hold-up volume Q1-Q2 / Q3-Q4	Weight
D62	11.5+1.72xn / 0.45+0.07xn	-196 °C/(-320 °F)	30 bar	(l): 0.081xn/2 / 0.081x(n-2)/2 (ft³): 0.003xn/2 / 0.003x(n-2)/2	2.92kg+0.145xn /
D62-E			435 psi	(l): 0.066xn/2 / 0.066x(n-2)/2 (ft³): 0.002xn/2 / 0.002x(n-2)/2	6.45lb+0.32xn
D62-H	11.5+1.44xn / 0.45+0.06xn	/	45 bar /	(l): 0.081xn/2 / 0.081x(n-2)/2 (ft³): 0.003xn/2 / 0.003x(n-2)/2	2.91kg+0.145xn /
D62L	13.5+1.72xn / 0.53+0.07xn				650 psi
D62L-E	13.5+1.44xn / 0.53+0.06xn	200 °C/(390 °F)	/	(l): 0.081xn/2 / 0.081x(n-2)/2 (ft³): 0.003xn/2 / 0.003x(n-2)/2	3.35kg+0.145xn /
D62L-H					650 psi

### Standard materials

Cover plates: AISI 304L

Connections: AISI 304L

Other material combinations are available on request. Please contact your Danfoss sales representative for more information.

Plates: AISI 316L

Brazing filler: Pure copper

### Third-party approvals

Europe: Pressure Equipment Directive (PED). America: Underwriters Laboratory Inc (UL). The third-party approvals stated are standard for all our products. For details of other existing approvals or to discuss how we can meet your local needs, please contact your Danfoss representative.

### Tech support

A number of easy-to-use online tools and the advanced heat exchanger software Hexact make it easier than ever to choose the right heat exchanger.

### Availability

A new logistics set-up with a full standard product range allows fast and reliable off-the-shelf deliveries. To see the full list of available standard products and configurations, use the QR code on the first page or contact your local sales representative.

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without consequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logo are trademarks of Danfoss A/S. All rights reserved.