

# PERFORMANCE DATA

Code No.	C-SBN373L8A
Power Source	3-PH 50Hz 380V
Condensing Temp.(°C)	30、35、40、45、50、54.4、60
Suction Gas Temp(°C)	18.3
Sub Cooled(K)	0
Compressor Cooling	Liquid Injection
Refrigerant	R404A

Capacity (W)

		Evaporating Temp. (°C)						
		-45	-40	-30	-20	-15	-10	-5
Condensing Temp. (°C)	30	2,560	3,160	4,810	7,340	9,070	11,200	13,830
	35	2,310	2,870	4,390	6,740	8,350	10,340	12,810
	40.0	2,090	2,600	4,010	6,190	7,680	9,540	11,860
	45.0	1,890	2,360	3,660	5,670	7,070	8,800	10,970
	50.0	1,710	2,140	3,330	5,200	6,500	8,120	10,140
	54.4			3,070	4,820	6,040	7,560	9,470
	60.0				4,380	5,500	6,910	8,690

Input (W)

		Evaporating Temp. (°C)						
		-45	-40	-30	-20	-15	-10	-5
Condensing Temp. (°C)	30	3,010	3,040	3,090	3,130	3,140	3,150	3,150
	35	3,380	3,410	3,450	3,480	3,490	3,500	3,510
	40.0	3,830	3,850	3,870	3,890	3,900	3,910	3,920
	45.0	4,350	4,360	4,360	4,370	4,370	4,380	4,380
	50.0	4,950	4,930	4,910	4,900	4,900	4,900	4,910
	54.4			5,450	5,420	5,410	5,410	5,420
	60.0				6,150	6,130	6,130	6,140

Current (A)

		Evaporating Temp. (°C)						
		-45	-40	-30	-20	-15	-10	-5
Condensing Temp. (°C)	30	4.8	4.8	4.9	4.9	5.0	5.0	5.0
	35	5.2	5.3	5.3	5.4	5.4	5.4	5.4
	40.0	5.8	5.8	5.8	5.8	5.9	5.9	5.9
	45.0	6.3	6.3	6.3	6.4	6.4	6.4	6.4
	50.0	6.9	6.9	6.9	6.9	6.9	6.9	6.9
	54.4			7.5	7.5	7.5	7.5	7.5
	60.0				8.2	8.2	8.2	8.2